Carpenterie Metalliche Anaunia S.r.l. Via C.Battisti, 8 - 38011 Sarnonico (TN) tel. 0463 832141	CE
Model	Compact
Version	V11
Length	2,42 [m]
Width	1,35[m]
Minimum platform height	1,00 [m]
Maximum platform height	2,80[m]
Total unladen mass (standard model)	2150 [Kg]
Batteries' voltage	48 [V]
Power of single traction motor	5 [kW]
Motor's power hydraulic pump	3 [kW]
Battery capacity	250 - 300 [Ah]
Hydraulic circuit capacity	16 [l]
Maximum hydraulic circuit pressure	210 [bar]
Payload on central platform	500 [kg]
Payload on lateral platforms - total	400 [kg] 4 persons
Maximum lateral platforms protrusion	60 [cm]
Payload on single lateral platform	200 [kg] 2 persons
Maximum lateral working slope	25%
Maximum longitudinal working slope	35%
Recharge's voltage	240 [V]
Maximum speed of wind	12,5 [m/s]

Kit facilitating belts for harvesting	
Width of single platform	40 [cm]
Length of single platform	110 [cm]
Payload single platform	200 [kg] 2 persons
Minimum platform height	120 [cm]
Maximum platform height	210 [cm]
Maximum platform protrusion	60 [cm]
Minimum width of machine (with closed platforms)	135 [cm]
Maximum width of machine (with platforms at maximum extensions)	255 [cm]
Maximum valid weight (to be loaded on frame)	800 [kg]
Payload of bins unloading lift	400[kg]